



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

List of Products Covered in Our LDC LP

Coaxial Cables

Lan Cables

Telephone Switchboard Cables

Telephone Dry Armoured Cables

Submersible Cables

Single Core Flexible Cables

Multicore Flexible Cables

Single Core XLPE Unarmoured/Armoured Cables

CCTV Cables

Fire Alarm Cables

Solar Cables

BMS Cables

Braided Cables

Steel Braided Cables

Speaker Cables

Welding Cables

Aluminium Service Wires

Instrumentation Cables

Rubber Cables

JFTC Unarmoured/Armoured Cables

RS 485 Cables

Fire Survival Cables

Festoon Cables

Uninyvin Cables

Optical Fibre Cables

FS Aluminium Cables



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAB INDUSTRIAL JELLY FLOODED COAXIAL CABLES

Polycab Gas Injected Physical Polyethylene Foam Insulation with Laminated Aluminium Tape and Aluminium Wire Braid, Jelly Flooded PVC Black Jacketed Industrial Coaxial Cables.

Size	100m Unarmoured	305m Unarmoured	1000m Flexible Armoured
RG - 59	1700	5185	77000
RG - 6	2170	6620	84000
RG - 11	4925	15020	119000
RG-6 CCS	1700	5185	74000
RG-11 CCS	3230	9850	109000

POLYCAB LAN (COMPUTER) CABLES

Polycab 4 Pair <u>Unshielded</u> Twisted Pair (UTP) LAN (Computer) Cables			Polycab 4 Pair <u>Shielded</u> Twisted Pair (STP) LAN (Computer) Cables	
	Unarmoured - Rate per 305 m	Flexible Armoured- Rate per 1000m	Unarmoured - Rate per 305 m	Flexible Armoured- Rate per 1000m
CAT 5 E	7155	85500	9950	97500
CAT 6	8700	96500	12500	106500
CAT 6 (GOLD)	10000		13200	



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAB INDUSTRIAL TELEPHONE (SWITCHBOARD) CABLES

Polycab High Conductivity Solid Annealed Bare Copper industrial Telephone (Switchboard) Cables with High Density Polyethylene Insulation, Paired, Polyester and Sheathed with High Oxygen Index, Fire Retardant, PVC Compound, Grey Outer Sheath generally conforming ITD Specification

No. of Pairs & Size	Rate / 100 Mtr. (Rs.)		Rate / 90 Mtr (Rs.)		Master Packing
	0.4 mm	0.5 mm	0.4 mm	0.5 mm	
1 Pair	610	860	550	775	20
2 Pair	1015	1435	915	1290	20
3 Pair	1500	2125	1350	1915	16
4 Pair	1875	2775	1690	2500	12
5 Pair	2300	3450	2070	3105	8
10 Pair		6690		6020	1
20 Pair		12500		11250	1
50 Pair		31800			1
100 Pair		61700			1

ARMoured TELEPHONE CABLES

No. of Pairs	Rate / 100m (0.5mm)	Master Packing
2 Pair	6600	Drums/Coils as required
5 Pair	10300	Drums/Coils as required
10 Pair	15100	Drums/Coils as required
20 Pair	19200	Drums/Coils as required
50 Pair	45200	Drums/Coils as required
100 Pair	89400	Drums/Coils as required

POLYCAB IND. 3C FLAT SUBMERSIBLE CABLES

Polycab PVC / Xlpe Insulated and PVC Sheathed Industrial 3 Core Flat Submersible Cable with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade 1100 Volts as per IS:694/2010

Size in Sq.mm.	PVC Insulated Rate per 100mtr. (Drum Packing - 500/1000 Mtrs.)	Xlpe Insulated Rate per 100mtr. (Drum Packing - 500/1000 Mtrs.)	PVC Insulated Rate Per 100mtr. (Corrogated Box Packing)
1.5	6550	6870	6300
2.5	10450	11000	9910
4	15200	15900	14700
6	22300	23400	21600
10	38600	39600	
16	61500	61700	
25	96200	96500	
35	133500	134000	
50	217400	228300	
70	302700	317800	
95	390800	410300	
120	499600	524600	
150	622400	653500	



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

Polycab FR Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Polycab PVC Insulated and PVC Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade 1100 Volts as per IS: 694:2010

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Rate/100m)		(Rate/100m)					
			Single Core	Packing	2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core
0.5	16/.2	5	665	25	2000	2625	3400	4	4350	5250
0.75	24/.2	8	950	25	2750	3590	4655	4	6130	7350
1	32/.2	13	1230	20	3325	4465	5730	4	7620	9100
1.5	30/.25	17	1800	16	4340	6100	7970	4	10500	12700
2.5	50/.25	24	2915	12	7035	9750	12870	3	17000	20400
4	56/.3	30	4450	8	10800	14900	19400		26600	31900
6	84/.3	38	6600	6	14900	22200	28100		41200	49000
10	80/.4	52	11400	1	26200	37200	48700		70500	
16	126/.4	70	18000	1	42400	59400	77200		112200	
25	196/.4	88	28200	1	68500	99000	128000		188200	
35	276/.4	110	39000	1	95500	137900	175000		260200	
50	396/.4	145	55500	1	134500	196600	250500		376800	
70	354/.5	215	80700	1	228200	273500	359800		525700	
95	484/.5	260	106700	1	252000	375100	485000		725600	
120	608/.5	305	140000	1	318800	467300	615000		942200	
150	750/.5	355	175000	1	398600	602200	790000		1154000	
185	925/.5	415	216000	1	491600	735700	982000		1408400	
240	1210/.5	500	280000	1	637700	960000	1270000		1855800	
300	1527/.5	585	350000	1	797100	1200000	1600000		2307800	
400	2036/.5	695	466600	1	1062800	1588000	2120000		3061500	



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

Polycab PVC Insulated, PVC Round Sheathed Multi Core Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			7 Core	8 Core	10 Core	12 Core
0.5	16/.2	5	6125	7000	8400	9900
0.75	24/.2	8	8270	9850	12000	13950
1	32/.2	13	10200	11800	14600	17100
1.5	30/.25	17	14450	18500	20200	24500
2.5	50/.25	24	23200	29300	33300	39500
4	56/.3	30	36800	43800	51600	62000
6	84/0.3	37	57800			

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	11900	13500	15800	19600
0.75	24/.2	8	16100	18500	21900	27700
1	32/.2	13	20400	23500	27700	35000
1.5	30/.25	17	28500	32500	38700	48500
2.5	50/.25	24	46900	53500	63600	79500

Polycab Multi Strand Bare Copper conductor XLPE insulated PVC Sheathed Cables					CCTV Cables (Rate/90m)	
Nominal Area	No/Dia of Strands	Current rating in Air at 40°C	Cu Conductor Unarmoured Cables	Cu Conductor Aluminium Armouring Cables	CCTV Cables 4+1	CCTV Cables 3+1
mm ²	No/mm		Rs/100 Mtr.	Rs/100 Mtr.	3520	3045
6	84/0.3	55	8600	11800	CCTV Armoured Cables (Rate/Km.)	
10	80/0.4	75	14400	20100	CCTV 4+1 Armoured	105000
16	126/0.4	103	21400	25100		
25	196/0.4	126	34000	38500		
35	276/0.4	152	46500	51600		
50	396/0.4	189	65000	71800	Fire Alarm System Arm Cables (Rate/Mtr)	
70	354/0.5	240	89700	98700	2 c x 1 Sq.mm. (Red)	90
95	484/0.5	297	121300	126700	2 c x 1.5 Sq.mm. (Red)	104
120	608/0.5	346	153600	160300		
150	750/0.5	390	191900	200400		
185	925/0.5	460	234100	241400		
240	1210/0.5	552	304100	318500		
300	1527/0.5	640	379200	400600		
400	2036/0.5	753	505800	530900		



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

Polycab FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Polycab PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade 1100 Volts as per IS: 694:2010

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Rate/100m)		(Rate/100m)					
			Single Core	Packing	2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core
0.5	16/.2	5	690	25	2150	2825	3655	4	4675	5645
0.75	24/.2	8	985	25	2955	3860	5000	4	6590	7900
1	32/.2	13	1275	20	3575	4800	6160	4	8190	9785
1.5	30/.25	17	1865	16	4560	6405	8370	4	11000	13300
2.5	50/.25	24	3015	12	7400	10200	13500	3	17900	21400
4	56/.3	30	4605	8	11300	15600	20400		27900	33500
6	84/.3	38	6830	6	15600	23300	29500		43300	51500
10	80/.4	52	11800	1	27500	39100	51100		74000	
16	126/.4	70	18600	1	44500	62400	81100		117800	
25	196/.4	88	29200	1	71900	104000	134400		197600	
35	276/.4	110	40400	1	100300	144800	183800		273200	
50	396/.4	145	57400	1	141200	206400	263000		395600	
70	354/.5	215	83500	1	239600	287200	377800		552000	
95	484/.5	260	110400	1	264600	393900	509300		761900	
120	608/.5	305	144900	1	334700	490700	645800		989300	
150	750/.5	355	181100	1	418500	632300	829500		1211700	
185	925/.5	415	223600	1	516200	772500	1031100		1478800	
240	1210/.5	500	289800	1	669600	1008000	1333500		1948600	
300	1527/.5	585	362300	1	837000	1260000	1680000		2423200	
400	2036/.5	695	482900	1	1115900	1667400	2226000		3214600	

**POLYCAB INDIA LIMITED**

LDC LP No. 02/2019-20 Dtd : 16th August 2019

Polycab PVC Insulated, FRLS Round Sheathed Multi Core Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			7 Core	8 Core	10 Core	12 Core
0.5	16/.2	5	6600	7525	9025	10650
0.75	24/.2	8	8900	10600	12900	15000
1	32/.2	13	11000	12700	15700	18400
1.5	30/.25	17	15150	19400	21200	25700
2.5	50/.25	24	24400	30700	35000	41500
4	56/.3	30	38500	46000	54200	65100
6	84/0.3	37	60700			

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	12800	14500	17000	21100
0.75	24/.2	8	17300	19900	23500	29800
1	32/.2	13	21900	25300	29800	37600
1.5	30/.25	17	29900	34100	40600	50900
2.5	50/.25	24	49200	56200	66800	83500



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAB SOLAR WIRES / CABLES

Flexible Tinned Copper Conductor/ Cross linkable (E Beam) LSZH Insulation/ Cross linkable (E Beam) LSZH Sheathed Solar Cable as per EN 50618		Flexible Tinned Copper Conductor Single Core Multistrand, Cross Linked, Zero Halogen Low Smoke Insulation and Cross Linked Low Smoke Sheathing, Heat Resistant upto 120°C and UV Resistant Solar Cables		Flexible Bare Copper Conductor Multistrand XLPE / PVC Insulated and UV Stabalized PVC Sheathed Single Core Solar Cables	
Size in Sq.mm.	Rate Per 100m	Size in Sq.mm.	Rate Per 100m	Size in Sq.mm.	Rate Per 100m
4	5660	4	5250	4	4810
6	8000	6	7700	6	7150
10	15900	10	15200	10	12900
16	23000	16	22100	16	19900
25	38100	25	36500		
35	53340	35	51100		
50	76200	50	73000		
70	106680	70	102200		
95	144780	95	138700		
120	182880	120	175200		
150	228600	150	219000		
185	281940	185	270100		
240	365760	240	350400		
300	457200	300	438000		

POLYCAB BUILDING MANAGEMENT SYSTEM CABLE (BMS)

Flexible Bare Copper Conductor, PVC Insulated,Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Rate/100m)

Cores	0.5 sq.mm (16/.2)	0.75 sq.mm (24/.2)	1.0 sq.mm (32/.2)	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)
2	4100	5100	6100	7500	11500
3	5100	6450	7800	10000	15500
4	6100	8100	9500	12600	19500
5	7100	9600	11500	15300	23700
6	8200	11100	13700	18000	27900
7	9400	12300	14700	19800	30700
8	10500	14100	17000	21500	33300
10	12000	16200	20500	28000	43400
12	14300	19000	23600	33500	51900
14	16500	23000	27000	38200	59200
16	18700	25300	32000	44000	68200
19	22000	29200	36600	51500	79800
24	25500	36300	46300	64000	99200

Packing - 100/300 Mtrs. Coils & 2000 Mtrs. Drums

Note : 3% Extra Charges for Drum Packing



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAB INDUSTRIAL BRAIDED CABLES

Polycab Annealed Bare Cu Flexible Conductor PVC Insulated, Tinned Cu Braided (Screened) PVC Sheathed Flexible Unarmoured Cables 1100 Volts. (Rate per 100 Mtr)

Cores	0.5 Sq.mm.	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm	4 sq.mm	6 sq mm	10 sq.mm	16 sq.mm
2	5000	6000	7200	8400	12700	20400	28800	45600	68400
3	6200	7900	8900	11300	16600	24500	34600	56200	85400
4	7900	9600	11800	13700	21100	31200	44400	81600	127200
5	10400	12700	15200	18500	27900				
6	11200	14500	17300	20300	33500				
7	12700	15500	18800	23600	38400				
8	14000	18300	21800	28200	47500				
10	16300	22100	25400	33300	57900				
12	19100	25400	29700	38100	67300				
14	21600	29500	35600	45700	78700				
16	23400	35600	38900	50800	87600				
19	29500	40100	45200	58400	101100				
24	36300	46500	57900	73700	128300				
Cores	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.		
2	172700	228600	315000	442000	566700	746800	930900		
3	219500	284500	400100	553200	729200	933500	1162800		



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAB MULTICORE STEEL BRAIDED CABLES (Rate / 100 M)

Flex Bare Copper Conductor,PVC Insulated, Cores Laid Up Together PVC Inner Sheathed, GI Wire Braided (Flexible Armouring), Overall PVC Sheathed Steel Braided Cables.

Cores	0.5 Sq.mm.	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm	4 sq.mm	6 sq mm
2	6600	7700	8700	10900	15400	21500	29400
3	7700	9500	10900	13800	20100	28600	40500
4	9300	11400	13300	17200	25200	38400	54600
5	10600	13500	16200	20700	30500		
6	12200	15600	18300	23900	35800		
7	13000	17000	20100	26500	40000		
8	14800	19100	22800	30200	45800		
10	18000	23600	27800	36800	56400		
12	20100	27000	32100	42900	66300		
14	23100	30200	36300	49300	75800		
16	25700	34500	41300	55700	86100		
19	29200	39800	48200	64900	100700		
24	37100	49300	60200	82200	126100		

Cores	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.	70 Sq.mm	95 Sq.mm.
2	47700	70500	106800	145000	205100	280400	374400
3	66300	99100	151300	206700	292800	403600	538700
4	90400	136500	209900	287300	408100	563100	754200

Note : 3% Extra Charges for Drum Packing

POLYCAB INDUSTRIAL SPEAKER WIRES

Speaker Wires (Oxygen Free) (Rate per 90 mtr)

Size	Price Per 90 Mtr.	Size	Price Per 90 Mtr.	Size	Price Per 90 Mtr.	Size	Price Per 90 Mtr.
23/36	1710	23/38	1205	0.5 Sq.mm	1565	1.5 Sq.mm	4100
40/36	2690	40/38	2010	0.75 Sq.mm	2215	2 Sq.mm	6080
70/36	4705	70/38	3155	1 Sq.mm	2870	2.5 Sq.mm	6695

** Flame Retardant, Heat Resistant up to 90°C & Oil Resistant

POLYCAB INDUSTRIAL WELDING CABLES

Polycab Flexible Copper Conductor 1100 Volts Welding Cable

Nominal Area of Conductor (sq mm)	Current Carrying Capacity	Conductor Constn. Strands/ Dia in mm	HOFR Insulation Rate/100m (Rs)
16	120	509/0.2	27300
25	160	796/0.2	40000
35	230	1115/0.2	55900
50	400	703/0.3	79400
70	600	999/0.3	110700
95	700	1346/0.3	149300
120	1100	1699/0.3	184400



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAB ALUMINIUM WIRES & CABLES

POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS <u>SOLID ALUMINIUM</u> CONDUCTOR WIRES AS PER IS 694		POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS <u>STRANDED ALUMINIUM</u> CONDUCTOR WIRES AS PER IS 694		POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE & THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE <u>STRANDED ALUMINIUM</u> CONDUCTOR SERVICE CABLES AS PER IS 694					
SQ.MM	RATE/ 100M	SQ.MM	RATE/ 100M	NO.OF CORES	SQ.MM	RATE/ 100M			
1.5	435	1.5	445	2	1.5	1610			
2.5	670	2.5	680	2	2.5	2280			
4	880	4	920	2	4	3220			
6	1340	6	1380	2	6	4210			
10	1990	10	2070	2	10	6530			
POLYCAB <u>SINGLE CORE</u> PVC INSULATED & <u>SHEATHED</u> 1100 VOLTS <u>STRANDED</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		16	2980	2	16	8650			
		25	4635	2	25	12300			
		35	6250	2	35	15700			
		50	8400	2	50	19900			
SQ.MM	RATE/ 100M	70	11200	2	70	19900			
1.5	660	95	13100	3	1.5	2200			
2.5	815	120	19000	3	2.5	3300			
4	1550	150	23600	3	4	4500			
6	2110	185	29300	3	6	6400			
10	2890	240	38100	3	10	9300			
16	4110	300	47500	3	16	12700			
25	5985	400	61000	3	25	17700			
35	7630	500	77600	3	35	23100			
50	10100	630	98300	3	50	29300			
POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE & THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE <u>SOLID ALUMINIUM</u> CONDUCTOR SERVICE CABLES AS PER IS 694				POLYCAB <u>XLPE</u> INSULATED AND <u>PVC</u> SHEATHED CABLE WITH EACH CORE HAVING <u>STRANDED ALUMINIUM</u> CONDUCTOR SERVICE CABLES GENERALLY CONFORMING TO IS 694.					
				NO.OF CORES	SQ.MM	RATE/ 100M	NO.OF CORES	SQ.MM	RATE/100M
				2	1.5	1495	2	4	2980
2	2.5	2185	2	6	4230				
2	4	2980	2	10	5255				
2	6	4135	2	16	7655				
2	10	6350							
3	1.5	2070							
3	2.5	3220							
3	4	4665							
3	6	5900							
3	10	9060							



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAB INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

OVERALL SHIELDED - ARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	82	0.75	94	1	103	1.5	123	2.5	166
CORE	3	0.5	94	0.75	109	1	124	1.5	155	2.5	211
CORE	4	0.5	108	0.75	127	1	149	1.5	187	2.5	261
CORE	5	0.5	120	0.75	145	1	171	1.5	218	2.5	309
CORE	6	0.5	136	0.75	164	1	196	1.5	251	2.5	361
CORE	7	0.5	144	0.75	177	1	213	1.5	275	2.5	399
CORE	8	0.5	162	0.75	199	1	239	1.5	312	2.5	451
CORE	10	0.5	189	0.75	235	1	287	1.5	375	2.5	551
CORE	12	0.5	210	0.75	264	1	325	1.5	431	2.5	619
CORE	14	0.5	232	0.75	297	1	365	1.5	490	2.5	716
CORE	16	0.5	256	0.75	330	1	411	1.5	551	2.5	803
CORE	19	0.5	290	0.75	375	1	469	1.5	634	2.5	936
CORE	24	0.5	351	0.75	460	1	559	1.5	770	2.5	1166
PAIR	1	0.5	81	0.75	92	1	100	1.5	121	2.5	164
PAIR	2	0.5	119	0.75	142	1	160	1.5	200	2.5	284
PAIR	3	0.5	142	0.75	173	1	201	1.5	258	2.5	374
PAIR	4	0.5	166	0.75	209	1	246	1.5	319	2.5	470
PAIR	5	0.5	193	0.75	245	1	291	1.5	383	2.5	560
PAIR	6	0.5	220	0.75	283	1	336	1.5	446	2.5	657
PAIR	7	0.5	239	0.75	309	1	372	1.5	498	2.5	743
PAIR	8	0.5	269	0.75	350	1	423	1.5	558	2.5	841
PAIR	10	0.5	321	0.75	410	1	502	1.5	676	2.5	1034
PAIR	12	0.5	361	0.75	474	1	584	1.5	791	2.5	1213
PAIR	14	0.5	390	0.75	533	1	660	1.5	906	2.5	1394
PAIR	16	0.5	443	0.75	598	1	744	1.5	1015	2.5	1581
PAIR	19	0.5	501	0.75	692	1	863	1.5	1184	2.5	1849
PAIR	24	0.5	625	0.75	864	1	1070	1.5	1486	2.5	2322
TRIAD	1	0.5	97	0.75	114	1	123	1.5	154	2.5	215
TRIAD	2	0.5	151	0.75	186	1	209	1.5	268	2.5	388
TRIAD	3	0.5	186	0.75	236	1	270	1.5	355	2.5	525
TRIAD	4	0.5	223	0.75	289	1	337	1.5	446	2.5	660
TRIAD	5	0.5	259	0.75	344	1	401	1.5	539	2.5	802
TRIAD	6	0.5	299	0.75	398	1	468	1.5	622	2.5	945
TRIAD	7	0.5	329	0.75	441	1	524	1.5	702	2.5	1074
TRIAD	8	0.5	370	0.75	485	1	587	1.5	797	2.5	1226
TRIAD	10	0.5	440	0.75	600	1	712	1.5	980	2.5	1511
TRIAD	12	0.5	500	0.75	690	1	833	1.5	1144	2.5	1788
TRIAD	14	0.5	568	0.75	788	1	955	1.5	1315	2.5	2060
TRIAD	16	0.5	630	0.75	880	1	1071	1.5	1488	2.5	2336
TRIAD	19	0.5	729	0.75	1021	1	1249	1.5	1740	2.5	2739
TRIAD	24	0.5	901	0.75	1277	1	1562	1.5	2191	2.5	3448
QUAD	1	0.5	108	0.75	130	1	147	1.5	186	2.5	265



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad/Quad laid up together with Al Inner sheathed Mylar/Drain Wire PVC Inner Sheathed Unrmoured PVC Outer Sheathed Instrumentation Cable.

OVERALL SHIELDED - UNARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	1	0.5	47	0.75	57	1	68	1.5	80	2.5	112
PAIR	2	0.5	74	0.75	92	1	112	1.5	157	2.5	214
PAIR	3	0.5	97	0.75	123	1	157	1.5	203	2.5	304
PAIR	4	0.5	112	0.75	157	1	203	1.5	259	2.5	394
PAIR	5	0.5	147	0.75	192	1	283	1.5	314	2.5	486
PAIR	6	0.5	168	0.75	214	1	304	1.5	383	2.5	573
PAIR	7	0.5	181	0.75	247	1	314	1.5	426	2.5	663
PAIR	8	0.5	203	0.75	271	1	371	1.5	486	2.5	754
PAIR	10	0.5	247	0.75	350	1	450	1.5	608	2.5	945
PAIR	12	0.5	295	0.75	404	1	530	1.5	720	2.5	1113
PAIR	14	0.5	325	0.75	462	1	608	1.5	821	2.5	1282
PAIR	16	0.5	383	0.75	516	1	697	1.5	945	2.5	1461
PAIR	19	0.5	439	0.75	617	1	809	1.5	1102	2.5	1720
PAIR	24	0.5	541	0.75	764	1	1011	1.5	1384	2.5	2180
TRIAD	1	0.5	63	0.75	71	1	89	1.5	110	2.5	162
TRIAD	2	0.5	104	0.75	126	1	158	1.5	204	2.5	303
TRIAD	3	0.5	138	0.75	169	1	215	1.5	283	2.5	427
TRIAD	4	0.5	170	0.75	213	1	275	1.5	362	2.5	558
TRIAD	5	0.5	206	0.75	257	1	336	1.5	446	2.5	694
TRIAD	6	0.5	240	0.75	304	1	396	1.5	530	2.5	822
TRIAD	7	0.5	271	0.75	344	1	451	1.5	606	2.5	946
TRIAD	8	0.5	308	0.75	393	1	514	1.5	697	2.5	1078
TRIAD	10	0.5	377	0.75	484	1	643	1.5	863	2.5	1340
TRIAD	12	0.5	439	0.75	573	1	755	1.5	1020	2.5	1590
TRIAD	14	0.5	502	0.75	658	1	872	1.5	1178	2.5	1841
TRIAD	16	0.5	574	0.75	747	1	989	1.5	1340	2.5	2104
TRIAD	19	0.5	670	0.75	873	1	1160	1.5	1574	2.5	2481
TRIAD	24	0.5	837	0.75	1095	1	1455	1.5	1993	2.5	3123
QUAD	1	0.5	68	0.75	84	1	108	1.5	147	2.5	214

**POLYCAB INDIA LIMITED**

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	157	0.75	171	1	197	1.5	240	2.5	329
PAIR	3	0.5	193	0.75	216	1	251	1.5	311	2.5	436
PAIR	4	0.5	230	0.75	263	1	308	1.5	388	2.5	540
PAIR	5	0.5	269	0.75	310	1	367	1.5	451	2.5	651
PAIR	6	0.5	309	0.75	360	1	426	1.5	534	2.5	763
PAIR	7	0.5	340	0.75	398	1	474	1.5	599	2.5	863
PAIR	8	0.5	386	0.75	439	1	530	1.5	679	2.5	985
PAIR	10	0.5	456	0.75	537	1	647	1.5	831	2.5	1209
PAIR	12	0.5	518	0.75	616	1	747	1.5	971	2.5	1424
PAIR	14	0.5	591	0.75	702	1	854	1.5	1106	2.5	1636
PAIR	16	0.5	662	0.75	790	1	961	1.5	1248	2.5	1851
PAIR	19	0.5	757	0.75	908	1	1111	1.5	1456	2.5	2163
PAIR	24	0.5	945	0.75	1141	1	1395	1.5	1837	2.5	2721
TRIAD	2	0.5	184	0.75	214	1	241	1.5	301	2.5	413
TRIAD	3	0.5	230	0.75	273	1	315	1.5	400	2.5	565
TRIAD	4	0.5	281	0.75	338	1	391	1.5	490	2.5	719
TRIAD	5	0.5	330	0.75	401	1	469	1.5	598	2.5	882
TRIAD	6	0.5	382	0.75	456	1	539	1.5	701	2.5	1036
TRIAD	7	0.5	422	0.75	509	1	605	1.5	793	2.5	1177
TRIAD	8	0.5	471	0.75	584	1	686	1.5	906	2.5	1343
TRIAD	10	0.5	566	0.75	706	1	841	1.5	1112	2.5	1669
TRIAD	12	0.5	656	0.75	821	1	983	1.5	1298	2.5	1956
TRIAD	14	0.5	741	0.75	933	1	1127	1.5	1498	2.5	2253
TRIAD	16	0.5	832	0.75	1051	1	1264	1.5	1694	2.5	2556
TRIAD	19	0.5	964	0.75	1222	1	1484	1.5	1992	2.5	2995
TRIAD	24	0.5	1209	0.75	1538	1	1872	1.5	2489	2.5	3791



POLYCAP INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAP INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

INDIVIDUAL & OVERALL SHIELDED - UNARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	97	0.75	112	1	137	1.5	168	2.5	237
PAIR	3	0.5	123	0.75	157	1	192	1.5	237	2.5	339
PAIR	4	0.5	157	0.75	192	1	237	1.5	304	2.5	439
PAIR	5	0.5	192	0.75	237	1	295	1.5	371	2.5	541
PAIR	6	0.5	225	0.75	283	1	350	1.5	439	2.5	643
PAIR	7	0.5	259	0.75	314	1	394	1.5	495	2.5	732
PAIR	8	0.5	295	0.75	359	1	450	1.5	573	2.5	844
PAIR	10	0.5	359	0.75	450	1	562	1.5	709	2.5	1034
PAIR	12	0.5	417	0.75	530	1	652	1.5	830	2.5	1237
PAIR	14	0.5	495	0.75	608	1	764	1.5	966	2.5	1428
PAIR	16	0.5	552	0.75	687	1	855	1.5	1102	2.5	1629
PAIR	19	0.5	643	0.75	809	1	1011	1.5	1292	2.5	1924
PAIR	24	0.5	809	0.75	1011	1	1272	1.5	1629	2.5	2417
TRIAD	2	0.5	133	0.75	150	1	183	1.5	230	2.5	332
TRIAD	3	0.5	177	0.75	206	1	253	1.5	320	2.5	470
TRIAD	4	0.5	223	0.75	263	1	325	1.5	416	2.5	617
TRIAD	5	0.5	271	0.75	317	1	396	1.5	508	2.5	759
TRIAD	6	0.5	315	0.75	375	1	469	1.5	610	2.5	901
TRIAD	7	0.5	357	0.75	426	1	537	1.5	697	2.5	1036
TRIAD	8	0.5	406	0.75	493	1	617	1.5	796	2.5	1183
TRIAD	10	0.5	508	0.75	607	1	761	1.5	985	2.5	1479
TRIAD	12	0.5	595	0.75	713	1	898	1.5	1162	2.5	1754
TRIAD	14	0.5	684	0.75	821	1	1036	1.5	1345	2.5	2030
TRIAD	16	0.5	770	0.75	931	1	1176	1.5	1528	2.5	2308
TRIAD	19	0.5	901	0.75	1091	1	1383	1.5	1809	2.5	2701
TRIAD	24	0.5	1129	0.75	1380	1	1748	1.5	2274	2.5	3422



LDC LP No. 02/2019-20 Dtd : 16th August 2019

LDC LP No. 02/2019-20 Dtd : 16th August 2019

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED, CPE OUTERSHEATHED ELASTOMERIC CABLE (Rate Per Mtr)

Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						326	489	660	921
2 Core	121	174	234	345	547	789			
3 Core	155	221	305	455	726	1068	1657	2225	3103
4 Core	192	279	389	594	931	1381	2149	2869	4011
5 Core	229	329	526	744	1184	1762	2646	3616	5013
6 Core	274	395	615	849	1352	2007	3285	4287	6023
7 Core	300	434	684	947	1515	2264	3553	4855	6851
8 Core	345	552							
10 Core	468	686							
12 Core	539	792							
14 Core	626	907							
16 Core	702	1013							
19 Core	807	1173							
24 Core	1031	1525							

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED, CPE OUTERSHEATHED ELASTOMERIC CABLE (Rate Per Mtr)

Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	1252	1673	2104	2591	3177	4077	5055	6675	
3 Core	4163	5557	6922	8563	10520	13495	16753	22076	
4 Core	5420	7225	9029	11180	13734	17660	21947	29188	



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMOURED POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	62	99	162	384	702	1376

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, G.S.TAPE ARMOURED POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	111	167	240	492	848	1578

**POLYCAB INDIA LIMITED**

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAB RS 485 CABLES (Armoured)500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	107
	22 AWG	0.32	113
	20 AWG	0.50	123
	18 AWG	0.80	137
	17 AWG	1.00	150
2 Pair	24 AWG	0.205	145
	22 AWG	0.32	161
	20 AWG	0.50	177
	18 AWG	0.80	217
	17 AWG	1.00	239

POLYCAB RS 485 CABLES (Un Armoured)500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	56
	22 AWG	0.32	64
	20 AWG	0.50	70
	18 AWG	0.80	86
	17 AWG	1.00	96
2 Pair	24 AWG	0.205	88
	22 AWG	0.32	102
	20 AWG	0.50	113
	18 AWG	0.80	147
	17 AWG	1.00	166

**POLYCAB INDIA LIMITED**

LDC LP No. 02/2019-20 Dtd : 16th August 2019

POLYCAB RS 485 CABLES (Armoured)500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	118
	22 AWG	0.32	124
	20 AWG	0.50	135
	18 AWG	0.80	151
	17 AWG	1.00	165
2 Pair	24 AWG	0.205	160
	22 AWG	0.32	177
	20 AWG	0.50	195
	18 AWG	0.80	239
	17 AWG	1.00	263

POLYCAB RS 485 CABLES (Un Armoured)500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	62
	22 AWG	0.32	70
	20 AWG	0.50	77
	18 AWG	0.80	95
	17 AWG	1.00	106
2 Pair	24 AWG	0.205	97
	22 AWG	0.32	112
	20 AWG	0.50	124
	18 AWG	0.80	162
	17 AWG	1.00	183



LDC LP Proposed for August

Fire Survival Cables

**Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Fibre Glass Tape Wrapped/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outersheathed
Fire Survival Cables**

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	217	271		330
2.5	271	346		427
4	318	417		522
6	412	552		698
10	583	797		1019
16	773	1079		1420
25	1102	1588	1912	2086
35	1466	2127	2459	2808
50	1933	2825	3313	3740
70	2686	3946	4617	5226
95	3531	5198	6072	6889
120	4393	6495	7739	8625
150	5379	7965	9203	10569
185	6645	9850	11531	13067
240	8449	12550	14667	16665
300	10467	15551	18148	20670
400	13626	20271	23494	26946



LDC LP Proposed for August

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Fibre Glass Tape Wrapped/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outsheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	243	298		361
2.5	298	375		459
4	347	446		555
6	442	584		734
10	618	833		1060
16	806	1114		1465
25	1144	1633	1962	2138
35	1511	2177	2514	2866
50	1983	2881	3374	3810
70	2748	4018	4695	5310
95	3601	5275	6157	6982
120	4467	6580	7842	8735
150	5468	8069	9319	10699
185	6745	9973	11670	13219
240	8570	12699	14834	16849
300	10609	15724	18342	20891
400	13804	20492	23742	27218



Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Fibre Glass Tape Wrapped/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	252	312		377
2.5	308	390		479
4	357	462		575
6	454	602		757
10	631	854		1087
16	822	1139		1498
25	1170	1673	2009	2191
35	1541	2221	2566	2925
50	2021	2938	3444	3886
70	2797	4092	4784	5409
95	3655	5357	6258	7091
120	4534	6680	7966	8869
150	5554	8198	9473	10872
185	6856	10139	11862	13438
240	8701	12898	15067	17114
300	10765	15957	18619	21203
400	13999	20784	24091	27608



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

FESTOON CABLES

(Rate/Mtr.)

Cores	0.5	0.75	1	1.5	2.5	4	6	10	16	25	35
3	40	51	63	83	134	204	296	493	763	1212	1661
4	52	67	84	112	177	271	397	660	1020	1613	2212
5	68	88	112	145	229	353					
6	81	106	132	172	277	424					
7	93	122	153	200	321	492					
8	108	139	173	231	369	566					
9	125	164	204	264	428	646					
10	138	180	225	292	473	722					
12	163	214	267	347	563	860					
14	198	252	314	415	662	1010					
16	224	292	363	470	760	1159					
18	245	320	406	527	841	1284					
24	335	436	551	713	1135	1743					



.DC LP No. 02/2019-20 Dtd : 16th August 2019

LDC LP No. 02/2019-20 Dtd : 16th August 2019

UNINYVIN CABLES

Multistranded Annealed Tinned Copper Conductor 105° C PVC Insulation with Nylon Braiding with Lacquer Coating Uninyvin Cables

Cable Size	Nom. Conductor Area (Sq.mm.)	Rate Per Mtr.
22	0.347	15.40
20	0.556	20.00
18	0.966	29.70
16	1.17	35.10
14	2.05	54.00
12	3.22	78.30
10	5.33	111
8	8.76	173
6	13.30	257
4	21.50	405
2	33.30	621
1	40.70	751
0	53.00	975
00	68.30	1242
000	84.20	1539
0000	109	1979



POLYCAB INDIA LIMITED

LDC LP No. 02/2019-20 Dtd : 16th August 2019

UNI-TUBE UN-ARMoured OPTICAL FIBRE CABLES

Cable Type	Fiber Type	Rate. Per Km.
2F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	20250
4F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	23500
6F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	26500
8F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	32400
12F UNI-TUBE OPTICAL FIBRE CABLES	Single Mode	37850
6F UNI-TUBE OPTICAL FIBRE CABLES	Multimode	47500
12F UNI-TUBE OPTICAL FIBRE CABLES	Multimode	81000

UNI-TUBE ARMoured OPTICAL FIBRE CABLES

Cable Type	Fiber Type	Rate. Per Km.
24F UNI-TUBE OPTICAL FIBRE CABLES	Multimode	152000



FS Aluminium Power Cables

Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/Xlpe Insulation/Wrapped with Fibre Tape Barrier/FRLS Inner Sheathed/GI Wire Armoured/FRLS Sheathed FS Aluminium Power Cables

(Rate/Mtr.)

Sq.mm.	3 Core	4 Core
16	424	548
25	571	728
35	691	892
50	855	1109
70	1169	1521
95	1461	1901
120	1746	2288
150	2077	2721
185	2517	3288
240	3133	4097
300	3770	4949
400	4692	6146

• The above rates are exclusive of GST which shall be charged extra.